



CIRCUIT DIAGRAM



Refer to additional specifications

RATING	DC50V 0.3A
CIRCUIT	6P2T
CONTACT RESISTANCE	100mΩ MAX.
TIMING	NON-SHORTING
OPERATING MODE	NON-LDCK
STROKE	FULL 2mm
OPERATING FORCE	300±100gf
OPERATING LIFE(cycles)	10,000

LONGCHUANG ZHONGYE (HK)CO.,LIMITED									
TITLE:			PART NO:						
PUSH SWITCH / HORIZONTAL			AP-62D01N						
DR: <i>Jacky</i> 2015/04/08			DWG NO: ADL-62D01						
CHKD: <i>Jacky</i> 2015/04/08			SCALE SHEET REV. CUSTOMER DRAWING						
APPD:			3/2 1/1 A						
									
UNITS mm									
WITHIN 1.5mm;±0.1mm									
OVER 1.5mm;±0.2mm									
MATERIAL									
SEE NOTE									
FINISH									
SEE NOTE									
Q'TY									
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF ACCURATE INNOTECH INC.									
8									
7									
6	SPRING	STEEL WIRE	1	NATURAL					
5	CONTACT CLIP	PBS STRIP	6	AG PLATED					
4	KNOB	ABS	1	BLACK					
3	FRAME	STEEL STRIP	1	NI PLATED					
2	BASE	PHENOLIC RESIN	1	NATURAL					
1	TERMINAL	BRASS STRIP	18	AG PLATED					
NO.	PARTS	MATERIAL	Q'TY	FINISHING					