




REV.	ECN.	NO.	APPD.


CIRCUIT DIAGRAM	MODEL CODE
	100
	101
	102
	103
	104
	105
	106
	107
	108
	109
	110

AT-1101RT-

	H
-	4.3
A	5.0



P.C.B MOUNTING PATTERN DIMENSION



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.25±0.1	
Operating Force	180±50gf	250±100gf
Operating Life(cycles)	30,000	

6	ADHESIVE TAPE	ADHESIVE TAPE			WITHIN 1.5mm:±0.1mm	UNITS mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED					
5	PAPER TAPE	PAPER			OVER 1.5mm:±0.2mm	MAT'L						
4	CONTACT	SUS	1	Ag CALD		SEE NOTE	TITLE:	PART NO.:				
3	CASE	NYLON+F.G/BRASS STRIP	1	Ag PLATED OVER Ni PLATED		FINISH	TACT SWITCH	AT-1101RT SERIES				
2	COVER	SUS	1	NATURAL	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.	SEE NOTE	DR:	Ricky 2017/08/01		DWG NO.:		
1	KNOB	NYLON+F.G	1	BLACK/WHITE/RED		Q'TY	CHKD:	Ricky 2017/08/01		AZJ-1101RT		
NO.	PARTS	MATERIAL	Q'TY	FINISHING			APPD:			SCALE	SHEET	REV.
								7:2		1/1	A	