



RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

P.C.B MOUNTING PATTERN DIMENSION

CIRCUIT DIAGRAM

ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

Rating	DC 12V 50mA	
Contact Resistance	100m Ω Max.	
Travel	0.3 $\pm$ 0.15mm	
Operating Force	160 $\pm$ 50gf	250 $\pm$ 100gf
Operating Life(cycles)	100,000	

5	SPRING PLATE	PBS	1	Ag CLAD	WITHIN 1.5mm $\pm$ 0.1	UNITS mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED			
4	TERMINAL	BRASS STRIP	4	Ag COATING	OVER 1.5mm $\pm$ 0.2					
3	CASE	NYLON+F.G	1	BLACK		SEE NOTE	TITLE: TACT SWITCH		PART NO.: AT-1103SE SERIES	
2	COVER	MILD STEEL	1	Ni COATING		FINISH SEE NOTE	DR: <i>Ricky</i> 2017/09/20		DWG NO.: AZJ-1103SE	
1	KNOB	NYLON+F.G	1	BLACK	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.	Q'TY	CHKD: <i>Ricky</i> 2017/09/20		SCALE	SHEET
NO.	PART NAME	MATERIAL	QTY.	FINISHING			APPD:		4:1	1/1
									A	CUSTOMER DRAWING