





DIMENSIONS



MODEL CODE

SK-12F14-GFI



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	0.5A 50V DC
CIRCUIT	1P2T
CONTACT RESISTANCE	100mΩ MAX.
TIMING	NON-SHORTING
TRAVEL	3mm
OPERATING FORCE	180±80gf
OPERATING LIFE(cycles)	10,000

8				WITHIN 1.5mm: ±0.1mm	UNITS	mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED			
7				OVER 1.5mm: ±0.2mm	MAT'L					
6	SPRING	STEEL STRIP	1	NATURAL	SEE NOTE					
5	CONTACT	BRASS STRIP	1	AG PLATED						
4	TERMINAL	BRASS STRIP	3	AG PLATED	FINISH		TITLE:	SLIDE SWITCH / HORIZONTAL	PART NO.:	SK-12F14
3	BASE	PHENOLIC RESIN	1	NATURAL	SEE NOTE		DR:	2016/06/22	DWG NO.:	ADL-12F14
2	KNOB	POM	1	BLACK			CHKD:	2016/06/22	SCALE	SHEET 1/1
1	FRAME	STEEL STRIP	1	NI PLATED	Q'TY		APPD:		REV.	A
ND.	PARTS	MATERIAL	Q'TY	FINISHING					CUSTOMER	DRAWING