



RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.







MODEL CODE

SS-12F24-GBG

Knob Type
GBG
VAA

L(mm)
~

DIMENSIONS



PCB LAYOUT
BOTTOM VIEW

CIRCUIT DIAGRAM

ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	0.5A 50V DC
CIRCUIT	1P2T
CONTACT RESISTANCE	100mΩ MAX.
TIMING	NON-SHORTING
TRAVEL	3mm
OPERATING FORCE	180±80gf
OPERATING LIFE(cycles)	10,000

8					WITHIN 1.5mm: ±0.1mm
7					OVER 1.5mm: ±0.2mm
6	SPRING	STEEL WIRE	1	NATURAL	
5	CONTACT	BRASS STRIP	1	Ag PLATED	
4	TERMINAL	BRASS STRIP	3	Ag PLATED	
3	BASE	PHENOLIC RESIN	1	NATURAL	
2	FRAME	STEEL STRIP	1	Ni PLATED	
1	KNOB	POM	1	BLACK	
NO.	PARTS	MATERIAL	Q'TY	FINISHING	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

UNITS	mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED			
MAT'L	SEE NOTE	TITLE: SLIDE SWITCH / VERTICAL			
FINISH	SEE NOTE	PART NO.: SS-12F24			
Q'TY	SEE NOTE	DR: Ricky 2015/07/08			
		CHKD: Ricky 2015/07/08			
		APPD:			
		SCALE	SHEET	REV.	CUSTOMER DRAWING
		3:1	1/1	A	