



DIMENSIONS

MODEL CODE

SS-23D11-GEE


Knob Type

GEE

VAC

L (mm)

--	--



CIRCUIT DIAGRAM

P.C.B LAYOUT

BOTTOM VIEW

ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	0.3A 50V DC
CIRCUIT	2P3T
CONTACT RESISTANCE	100mΩ MAX.
TIMING	NON-SHORTING
TRAVEL	2mm
OPERATING FORCE	250±100gf
OPERATING LIFE(cycles)	10,000

8					WITHIN 1.5mm: ±0.1mm	UNITS mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED				
7					OVER 1.5mm: ±0.2mm	MAT'L	TITLE:		PART NO.:		
6	SPRING PLATED	PBS STRIP	1	NATURAL		SEE NOTE	SLIDE SWITCH / VERTICAL		SS-23D11		
5	CONTACT CLIP	PBS STRIP	2	Ag PLATED			DR:	2015/05/28		DWG NO.:	
4	TERMINAL	BRASS STRIP	6	Ag PLATED			CHKD:	2015/05/28		ADL-23D11	
3	BASE	PHENOLIC RESIN	1	NATURAL	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE, INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.	FINISH					
2	FRAME	STEEL STRIP	1	Ni PLATED		SEE NOTE					
1	KNOB	POM	1	BLACK		Q'TY					
NO.	PARTS	MATERIAL	Q'TY	FINISHING			APPD:	7/2	1/1	A	CUSTOMER DRAWING