



- SPECIFICATION**
1. Rating : DC 30V 0.5A ;
  2. Contact resistance :  $\leq 30m\Omega$  ;
  3. Insulation resistance :  $\geq 100M\Omega$  ;
  4. Withstand voltage : 500VAC ;
  5. Insertion and extraction force : 3-20N
  6. Life test : 5,000 cycles .

MODEL NO.	P1-2595-S124	P1-2594A-S124	P1-2594B-S124	P1-2593-S124
SCHEMATIC				

NO.	DESCRIPTION	QTY	MATERIAL
7	COVER	1	PA9T
6	HOUSING	1	PA9T
5	5# CONTACT FOOT	1	BRASS
4	4# CONTACT FOOT	1	BRASS
3	3# CONTACT FOOT	1	PHOSPHOR BRONZE
2	2# CONTACT FOOT	1	PHOSPHOR BRONZE
1	1# CONTACT FOOT	1	PHOSPHOR BRONZE

**LONGCHUANG ZHONGYE (HK)CO.,LIMITED**

ITEM NO.	DESCRIPTION	DRAWN	DATE	3RD. ANGELS	UNITS	MM	DATE	DATE	SHEET NO.	PART NO.	SIZE
1	更新尺寸	Jack	031518				03/15/18	03/15/18	1 of 1	P1-259x-S124	A4
<p>TOLERANCE UNLESS OTHERWISE STATED : Above 5 ~ 15 <math>\pm 0.3</math> Above 15 ~ 30 <math>\pm 0.4</math> Above 30 ~ 50 <math>\pm 0.5</math> Angle <math>\pm 0.3</math></p>											