RoHS Compliant 2002/95/EC

Process Capable

REV.	ECN. NO.	APPD.













A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

NOTES:

1. ELECTRICAL:
   1) CURRENT RATING:3AMP;
   2) INSULATION RESISTANCE: 100MΩMIN;
   3) CONTACT RESISTANCE: 30mΩMAX;
   4) WITHSTANDING VOLTAGE: 250V AC;
   5) OPERATING TEMPERATURE:-30°C TO +80°C.
2. Mechanical:
   1) Mating Force: 35N MAX
   2) Unmating Force: 10N MIN.
3. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.
4. PART NO.

USCF-24*N-4BV61

- W:WHITE, B:BLACK
- 1:Au 1U", 2:Au 3U", 5:Au 15U", 6:Au 30U"
- 1:PBT, 2:PA6T, 3:PA9T, 4:LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING
5	SHRAPNEL	STAINLESS STEEL	2	
4	HOOK	STAINLESS STEEL	1	
3	SHELL	STAINLESS STEEL	1	PLATED NICKEL
2	TERMINAL	COPPER ALLOY	24	PLATED GOLD
1	HOUSING	LCP+30%GF	1	UL94V-0

X. ±0.35	X.° ±2°
.X ±0.3	.X° ±1°
.XX ±0.25	.XX°
.XXX ±0.15	.XXX°

UNITS mm

MAT'L SEE NOTE

FINISH SEE NOTE

Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

LONGCHUANG ZHONGYE (HK)CO.,LIMITED

TITLE: USB 3.1Type-C/F 前插后贴板上母座 后盖有缺口成品

PART NO.: USCF-24*N-4BV61

DR: gan 2015/11/25

CHKD: gan 2015/11/25

APPD:

DWG NO.: AII-V61

SCALE	SHEET	REV.	
1:1	1/1	B	CUSTOMER DRAWING

龙创中业 开关‖插座‖连接器 LCZY SWITCH‖ JACK ‖ CONNECTOR