



RECOMMENDED PCB LAYOUT



NOTES:

1. ELECTRICAL:

- 1) VOLTAGE CURRENT RATING:2AMP,30V AC;
- 2) INSULATION RESISTANCE: 1000MΩ MIN;
- 3) CONTACT RESISTANCE: 30mΩ MAX;
- 4) WITHSTANDING VOLTAGE: 500V AC;
- 5) OPERATING TEMPERATURE:-55°C TO +85°C.

4.PART NO.

USAF-04*N-1*RU00

1Au 1u*
6Au 30u*
V/WHITE
B/BLACK
1PBT
2PA6T
3PA9T
4LCP

- 2. Mechanical:
 - 1) Mating Force: 35N MAX
 - 2) Unmating Force: 10N MIN.
- 3. NOTE:1.DIMENSIONS MARKED "▲"
TO BE CHECKED BY Q.C & IPQC.

Bill of materials:

3	HOUSING	PBT	1	UL94V-0
2	SHELL	COPPER ALLOY	1	PLATED NICKEL
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN
NO	PARTS	MATERIAL	QTY	FINISHING

X: ±0.35	X: ±2°	UNITS	mm
.X ±0.3	.X' ±1°	MAT'L	
.XX ±0.25	.XX'	SEE NOTE	
.XXX ±0.15	.XXX'	FINISH	
		SEE NOTE	

LONGCHUANG ZHONGYE (HK)CO.,LIMITED			
TITLE:		PART NO.:	
USB AF 短体正向(两脚) 无卷边		USAF-04*N-1*RU00	
DR: gan 2015/7/14		DWG NO.:	
CHKD: gan 2015/7/14		A11-RU00	
APPD:		SCALE SHEET REV. B	
1:1		CUSTOMER DRAWING	