







RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



RECOMMENDED PCB LAYOUT



NOTES:

1. ELECTRICAL:

- VOLTAGE CURRENT RATING: 2AMP, 30V AC;
- INSULATION RESISTANCE: 1000M Ω MIN;
- CONTACT RESISTANCE: 30m Ω MAX;
- WITHSTANDING VOLTAGE: 500V AC;
- OPERATING TEMPERATURE: -55°C TO +85°C.

2. Mechanical:

- Mating Force: 35N MAX
- Unmating Force: 10N MIN.

3. NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.

USAF-04*N-1*R801

1: Au 1U"
6: Au 30U"

W: WHITE
B: BLACK
1: PBT
2: PA6T
3: PA9T
4: LCP

Bill of materials:

3	HOUSING	PBT	1	UL94V-0	X. ± 0.35	X.* $\pm 2^{\circ}$	UNITS mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED							
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.X ± 0.3	.X.* $\pm 1^{\circ}$	MAT'L	TITLE: USB A/F 90° DIP 短体铜壳(10.6反向)		PART NO.: USAF-04*N-1*R801					
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.XX ± 0.25	.XX*	SEE NOTE	FINISH		DR: gan 2012/7/03		DWG NO.: AII-R801			
NO	PARTS	MATERIAL	QTY	FINISHING	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.	.XXX ± 0.15	.XXX*	SEE NOTE	CHKD: gan 2012/7/03		SCALE		SHEET	REV.	CUSTOMER DRAWING
								Q'TY	APPD:		1:1		1/1	B	
															