





RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



NOTES:

1. ELECTRICAL:

- VOLTAGE CURRENT RATING: 2AMP, 30V AC;
- INSULATION RESISTANCE: 1000MΩ MIN;
- CONTACT RESISTANCE: 30mΩ MAX;
- WITHSTANDING VOLTAGE: 500V AC;
- OPERATING TEMPERATURE: -55°C TO +85°C.

2. Mechanical:

- Mating Force: 35N MAX
- Unmating Force: 10N MIN.

3. NOTE: 1. DIMENSIONS MARKED "▼"
TO BE CHECKED BY Q.C & IPQC.

4. PART NO.

USAF-04*N-1*C82

W: WHITE
B: BLACK
1: Au 1U"
6: Au 30U"
1: PBT
2: PA6T
3: PA9T
4: LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm	LONGCHUANG ZHONGYE (HK) CO., LIMITED			
5	BOTTOM COVER	PBT+30%GF	1	UL94V-0	X. ±0.35	X.* ±2°	TITLE: USB AF 90度 加后包(弯脚7.70 带后塞) 侧插长体 PART NO.: USAF-04*N-1*C82 DWG NO.: AII-C82 DR: gan 2012/12/13 CHKD: gan 2012/12/13 APPD: 1:1 1/1 B CUSTOMER DRAWING			
4	HOUSING	PBT+30%GF	1	UL94V-0	.X ±0.3	.X* ±1°				
3	BACK COVER	SPCC	1	PLATED NICKEL	.XX ±0.25	.XX*				
2	SHELL	COPPER ALLOY/SPCC	1	PLATED NICKEL	.XXX ±0.15	.XXX*				
1	TERMINAL	COPPER ALLOY	4	Plated Gold in Mating Area; Tin on Solder Tails	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.					
NO	PARTS	MATERIAL	QTY	FINISHING						