

Pb Process Capable RoHS Compliant 2002/95/EC						REV		LTR		DESCRIPTION		DATE		APPROVED	

14.00

14.50

12.50

5.12

13.45

7.00

1.20

6.00

1.20

7.10

3.00

0.65

2.00

7.00

7.00

2.00

1.20

0.89

13.45

2.12

4-Ø0.85

RECOMMENDED PCB LAYOUT

LCZY SWITCH JACK

龙创中业

连接器

NOTES:

1. ELECTRICAL:

1) VOLTAGE CURRENT RATING:2AMP,30V AC;

2) INSULATION RESISTANCE: 1000MΩ MIN;

3) CONTACT RESISTANCE: 30mΩ MAX;

4) WITHSTANDING VOLTAGE: 500V AC;

5) OPERATING TEMPERATURE:-55°C TO +85°C.

2. Mechanical:

1) Mating Force: 35N MAX

2) Unmating Force: 10N MIN.

3. NOTE:1.DIMENSIONS MARKED "▼"

TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

USAF-04*N-1*R616

1:Au 1U"

6:Au 30U"

W:WHITE

B:BLACK

1:PBT

2:PA6T

3:PA9T

4:LCP

Bill of materials:

3	HOUSING	PBT	1	UL94V-0	X. ±0.35	X.* ±2*	UNITS	mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED					
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.X ±0.3	.X* ±1*	MAT'L		TITLE:		PART NO.:			
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.XX ±0.25	.XX*	FINISH		USAF AF 90度DIP 沉板2E长脚(14.0)		USAF-04*N-1*R616			
					.XXX ±0.15	.XXX*	SEE NOTE		DR: gan 2012/6/29		DWG NO.:			
					THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC		Q'TY		CHKD: gan 2012/6/29		AII-R616			
								APPD:		SCALE		SHEET	REV.	CUSTOMER DRAWING
										1:1		1/1	B	

1

2

3

4

5

6

7