










REV.	ECN.	NO.	APPD.



1. ELECTRICAL:

- 1) VOLTAGE CURRENT RATING: 2AMP,30V AC;
- 2) INSULATION RESISTANCE: 1000M Ω MIN;
- 3) CONTACT RESISTANCE: 30m Ω MAX;
- 4) WITHSTANDING VOLTAGE: 500V AC;
- 5) OPERATING TEMPERATURE:-55° C TO +85° C.

2. Mechanical:

- 1) Mating Force: 35N MAX
- 2) Unmating Force: 10N MIN.

3. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

USAF-04*N-1*R603

$$\begin{array}{r} 1: Au \quad 1U'' - \\ 6: Au \quad 30U'' \end{array}$$

— W:WHITE
B:BLACK
— 1:PBT
2:PA6T
3:PA9T
4:CP

Bill of materials:

3	HOUSING	PBT	1	UL94V-0	X. ±0.35	X.* ±2*	UNITS mm	LONGCHUANG ZHONGYE (HK)CO.,LIMITED								
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.X ±0.3	.X* ±1*	MAT'L	SEE NOTE	TITLE: USB AF 90° DIP直脚 无后盖			PART NO.: USAF-04*N-1*R603				
					.XX ±0.25	.XX*										
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.XXX ±0.15	.XXX*	FINISH	SEE NOTE	DR: <i>gan</i> 2012/6/29			DWG NO.: AII-R603				
					THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.											
NO	PARTS	MATERIAL	QTY	FINISHING			Q'TY		APPD:				SCALE	SHEET	REV.	CUSTOMER DRAWING
													1:1	1/1	B	