


- NOTES:
1. ELECTRICAL:
- 1) VOLTAGE CURRENT RATING: PIN 8 5 1.8AMP MAX / PIN 2 & 3 4 1AMP MAX, 30V AC;
- 2) INSULATION RESISTANCE: 100MΩ MIN;
- 3) CONTACT RESISTANCE: 30mΩ MAX;
- 4) WITHSTANDING VOLTAGE: 100V AC; FOR 1 MIN.
- 5) OPERATING TEMPERATURE: -30°C TO +80°C.
2. Mechanical:
- 1) Mating Force: 35N MAX
- 2) Unmating Force: 10N MIN.
3. DIMENSIONS MARKED "▲" TO BE CHECKED BY Q.C & IPQC.

RECOMMENDED PCB LAYOUT



Bill of materials:				LONGCHUANG ZHONGYE (HK)CO.,LIMITED			
3	SHELL	COPPER ALLOY	1	PLATED TIN	UNITS	mm	PART NO.:
2	HOUSING	LCP+30%GF	1	UL94V-0	MAT'L		MUYF-05XT-4BHUA317
1	TERMINAL	COPPER ALLOY	5	PLATED GOLD	SEE NOTE		
ND	PARTS	MATERIAL	QTY	FINISHING	FINISH	SEE NOTE	
					Q'TY		
					DR: 2018/9/19		
					CHKD: 2018/9/19		
					APPD: 2018/9/19		
					SCALE	SHEET	REV.
					5:1	1/1	A
					CUSTOMER DRAWING		