

REV.	ECN.	NO.	APPD.

RoHS

Compliant

2002/95/EC

Process
Capable

Halogen Free

RECOMMENDED PCB LAYOUT

不锈钢双铆合

铜壳铆合

NOTES:

- ELECTRICAL:
 - VOLTAGE CURRENT RATING: PIN 1 & 5 1.8AMP MAX / PIN 2 & 3 & 4 1AMP MAX, 30V AC;
 - INSULATION RESISTANCE: 100MΩ MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 100V AC FOR 1 MIN.
 - OPERATING TEMPERATURE: -30°C TO +80°C.
- Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
- DIMENSIONS MARKED "▲" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.

MUYF-05*1-4BHUA067

1AU 1U" 1AU 1U" 6AU 30U"

T-TIN NICKEL

1.PBT 2.PA6T 3.PA9T 4.LCP

W/WHITE B/BLACK

Bill of materials:

3	SHELL	STAINLESS STEEL	1	PLATED TIN	X: ±0.35	X': ±2"	UNITS	mm	TITLE:	LONGCHUANG ZHONGYE (HK) CO., LIMITED				
2	HOUSING	LCP+30%GF	1	UL94V-0	X: ±0.30	X': ±1"	MAT'L		MICRO USB B TYPE F 5P	PART NO.: MUYF-05XT-4BHUA067				
1	TERMINAL	COPPER ALLOY	5	PLATED GOLD	.XX ±0.25	.XX'	SEE NOTE		四脚全插牛角型短针	DWG NO.: A11-HUA067				
ND	PARTS	MATERIAL	QTY	FINISHING	.XXX ±0.15	.XXX'	FINISH	Q'TY	DR: Ricky 2018/9/4	CHKD: Ricky 2018/9/4	SCALE	SHEET	REV.	CUSTOMER
1									APPD:		5:1	1/1	A	DRAWING