






REV.	DESCRIPTION	DATE
A/0	新版发行	2016.11.28

技术要求:


- 1、塑件材料: LCP (UL-94V-0)
- 2、接触件: 黄铜镀锡
- 3、接触电阻: $\leq 30\text{m}\Omega$
- 4、绝缘电阻: $\geq 1000\text{M}\Omega$
- 5、额定电压: 250V AC DC
- 6、额定电流: 7.0A AC DC
- 7、耐压: 能承受1000V AC/Min ute
- 8、工作温度: $-25^{\circ}\sim +85^{\circ}$
- 9、可焊性试验: 浸锡面积 $\geq 95\%$ 温度260,时间
2.5 ± 0.5 秒
- 10、铅和镉等六大有害物质含量要符合环保要求




SECTION A-A

VH-3.96-XP-WT

P/n	A	B	C
2	3.96	9.8	8.6
3	7.92	13.76	12.56
4	11.88	17.72	16.52
5	15.84	21.68	20.48
6	19.8	25.64	24.44
7	23.76	29.6	28.4
8	27.72	33.56	32.36
9	31.68	37.52	36.32
10	35.64	45.44	40.28



SUGGESTED PCB LAYOUT
(COMPONENT SIDE)



SUGGESTED PCB LAYOUT
(COMPONENT SIDE)

3	焊片 Fitting Nail	黄铜	2	电鍍(锡): 整个表面电鍍30u"MIN, 厚度 80u"MIN.
2	端子 Contact	黄铜	n x 1	电鍍(锡): 整个表面电鍍30u"MIN, 厚度 80u"MIN.
1	基板 Wafer	LCP (UL94V-0)	1	材料
序号	名称	材料	数量	附注

GENERAL TOLERANCES				DRAWN BY 绘图者		龙创中业电子科技(东莞)有限公司	
0.X	± 0.25	X. [°]	$\pm 3^{\circ}$	CHK. BY 审核者			
0.XX	± 0.12			APRV. BY 批准人		SHEET	PROD. NAME
0.XXX	± 0.05	X.X [°]	$\pm 0.5^{\circ}$	DRAWING NO.	10P1	PART NO. VH-3.96-XP-WT	
UNIT	SIZE	SCALE		006-0082-001	TITLE		
MM	A4	1:1					

借用登记

旧底图总号

底图总号

签字

日期