





RoHS



Circuit Diagram



function(功能) :




NO.1	
PART NO	
L	自锁
N	无锁

Material:

Button 按钮	POM
crochet hook钩针	不锈钢 (复银)
spring 弹簧	黄铜 (镀银)
Base 底座	PA66/尼龙
Pin 引脚	铜 (镀银)
Upper cover上盖	POM

Main technical specifications:

Rated load(额定负荷):	DC 30V 0.1A
Contact impedance(接触阻抗):	≤100mΩMAX
Insulation impedance(绝缘阻抗):	≥100MΩMIN
Welding resistance temperature(耐焊温度):	250±5 ° 5s
OPERATING LIFE (电气寿命):	10,000 cycles
Usage temperature (使用温度):	-25 °C to 80 °C
Operating humidity (使用湿度):	≤85% RH
Trip(行程):	2.4±0.3mm
Operating force(操作力):	1 2 3 4 5 6 250±100g
NO.2	



PCB Layout(Pattern Side)

public errand (公差) : ±0.2mm unit (单位) : mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	SWITCH			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	K8-8484F			CHECK	Z.LIU	REV.	A1
	UNIT :	TOLERANCE	UP TO 5	ANGLE	APPROVAL	DATE	K8-09-2019
	mm	OTHERWISE	ABOVE 5 ~30	0°±3°	SCALE	PAGE	1 OF 1

K8-8484F-□-□