







RoHS








电路示意图



P.C.B 设计参考尺寸

public errand (公差) : ±0.2mm unit (单位) : mm



function(功能) :

NO.1	
PART NO	
L	自锁
N	无锁

Material:

Button 按钮	PBT
crochet hook钩针	不锈钢 (复银)
spring 弹簧	黄铜 (镀银)
Base 基座 /外壳	PA66
Pin 引脚	铜 (镀银)
Upper cover上盖	PPA

Main technical specifications:

Rated load(额定负荷):	DC 12V 0.05A
Contact impedance(接触阻抗):	≤100mΩ MAX
Insulation impedance(绝缘阻抗):	≥100MΩ MIN
Welding resistance temperature(耐焊温度):	250±5 ° 5s
OPERATING LIFE (电气寿命):	20,000 cycles
Usage temperature (使用温度):	-25 °C to 80 °C
Operating humidity (使用湿度):	≤85% RH
Trip(行程):	1.5±0.2mm
Operating force(操作力):	1 2 3 4 5 6 250±50gf

NO.2

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	SWITCH			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	K8-5851DM			CHECK	Z.LIU	REV.	A1
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5 ABOVE 5 ~30 ABOVE 30 ANGLE	±0.2 ±0.3 ±0.5 ±3°	APPROVAL	DATE		K8-09-2019
				SCALE	2:1	PAGE	1 OF 1

K8-5851DM-□-□