











RoHS



P. C. B LAYOUT

public errand (公差) : ±0.2mm unit (单位) : mm

function(功能) :

NO.1	
PART NO	
L	自锁
N	无锁

Material:

Button 按钮	PPA
crochet hook钩针	不锈钢 (复银)
spring 弹簧	黄铜 (镀银)
Base 底座	PPA
Pin 引脚	铜 (镀银)
Upper cover上盖	PA66

Main technical specifications:

Rated load(额定负荷):	DC 30V 0.5A
Contact impedance(接触阻抗):	≤100mΩ MAX
Insulation impedance(绝缘阻抗):	≥100MΩ MIN
Welding resistance temperature(耐焊温度):	250±5 ° 5s
OPERATING LIFE (电气寿命):	20,000 cycles
Usage temperature (使用温度):	-25 °C to 80 °C
Operating humidity (使用湿度):	≤85% RH
Trip(行程):	1.5±0.2mm
Operating force(操作力):	1 2 3 4 5 6 200±50gf

NO.2

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING		G.L CHEN		DWG.No.		LCZY	
PART NO.		K8-5851EX		CHECK		Z.LIU		REV.		A1	
	UNIT :	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE	K8-09-2019	PAGE	1 OF 1	
			ABOVE 5 ~30	±0.3							
	mm		ABOVE 30	±0.5	0°±3°	SCALE	2:1				
			ANGLE	±3°							

K8-5851EX-□-□