






RoHS



Height(高度) :

NO.1	
PART NO	H
D	7.3
F	

Material:

Button 按钮	PPA/LCP
Cover plate 盖板	铁 (镀银)
Shrapnel 弹片	不锈钢 (复银)
Base 底座	PPA/LCP
Pin 引脚	磷铜 (镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA			
Contact impedance(接触阻抗):	≤100mΩ MAX			
Insulation impedance(绝缘阻抗):	≥100MΩ MIN			
Welding resistance temperature(耐焊温度):	250±5 ° 5s			
OPERATING LIFE(电气寿命):	100,000 cycles			
Usage temperature(使用温度):	-25 °C to 85 °C			
Operating humidity(使用湿度):	≤85% RH			
Trip(行程):	0.35 ± 0.1mm			
Operating force(操作力):	1	90 ± 30gf	2	130 ± 30gf
	3	180 ± 50gf	4	250 ± 50gf
	5	350 ± 50gf	6	
	NO.2			

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

public errand (公差) : ±0.2mm unit (单位) : mm

PART NAME		SWITCH		DRAWING		G.L CHEN		DWG.No.		LCZY	
PART NO.		K2-1103ST		CHECK		Z.LIU		REV.		A1	
	UNIT : mm	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL	SCALE	DATE	PAGE	K2-09-2019	1 OF 1
			ABOVE 5 ~30	±0.3							
			ABOVE 30	±0.5							
			ANGLE	±3°							

K2-1103ST-□-□

B

A