

RoHS

Height(高度) :NO.1

NO.1				
PART NO	L1	L2	H1	H2
A: 双联上5下5	1.4	1.4	3.65	3.65
B: 双联上5下10	1.4	6.4	3.65	8.65
C: 双联上7下10.5	3.4	6.9	5.65	9.15
D: 双联上10下5	6.4	1.4	8.65	3.65
E: 双联上10下7	6.4	3.4	8.65	5.65
F: 双联上10下10	6.4	6.4	8.65	8.65
G: 双联上11.5下11.5	7.9	7.9	10.15	10.15
M: 双联上11.5下17	7.9	13.4	10.15	15.65
N: 双联上17下17	13.4	13.4	15.65	15.65

Material:

Button 按钮	PPA/LCP
Cover plate 盖板	铁 (镀银)
Shrapnel 弹片	不锈钢 (复银)
Base 底座	PPA/LCP
Pin 引脚	磷铜 (镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA			
Contact impedance(接触阻抗):	≤ 100mΩ MAX			
Insulation impedance(绝缘阻抗):	≥ 100MΩ MIN			
Welding resistance temperature(耐焊温度):	250 ± 5 ° 5s			
OPERATING LIFE (电气寿命):	50,000 cycles			
Usage temperature (使用温度):	-25 to 85			
Operating humidity (使用湿度):	≤ 85% RH			
Trip(行程):	0.2 ± 0.1mm			
Operating force(操作力):	1	90 ± 30gf	2	130 ± 30gf
	3	180 ± 50gf	4	250 ± 50gf
	5	350 ± 50gf	6	

NO.2

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		SWITCH				DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.		K2-1122DQ				CHECK	Z.LIU	REV.	A1
	UNIT :	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL		DATE	K2-09-2019
	mm		ABOVE 5 ~30	±0.3					
			ABOVE 30	±0.5					
			ANGLE	±3°	SCALE	2:1	PAGE	1 OF 1	

K2-1122DQ-□-□