




RoHS

Height(高度) :NO.1



	J		T
	I		S
	H		R
	G		Q
	F		P
	E		O
	D		N
	C		M
	B		L
1.5	A		K
高度H(mm)	X=	高度H(mm)	X=



PCB Layout



Circuit Diagram



Material:

Button 按钮	PPA/LCP耐温280°C
Cover plate 盖板	铜 (镀银)
Shrapnel 弹片	不锈钢 (复银)
Base 基座	PPA/LCP耐温280°C
Pin 引脚	磷铜 (镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA
Contact impedance(接触阻抗):	≤100mΩ MAX
Insulation impedance(绝缘阻抗):	≥100MΩ MIN
Welding resistance temperature(耐焊温度):	250±5 ° 5s
OPERATING LIFE (电气寿命):	100,000 cycles
Usage temperature (使用温度):	-25 °C to 85 °C
Operating humidity (使用湿度):	≤85% RH
Trip(行程):	0.15±0.1mm
Operating force(操作力):	1 90±30gf 2 130±30gf 3 180±50gf 4 250±50gf 5 350±50gf 6

NO.2

public errand (公差) : ±0.2mm unit (单位) : mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

PART NAME	SWITCH			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	K2-1127SN			CHECK	Z.LIU	REV.	A1
	UNIT :	TOLERANCE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE
	mm	OTHERWISE	ABOVE 5 ~30	±0.3	0°±3°	SCALE	K2-09-2019
			ABOVE 30	±0.5			PAGE
			ANGLE	±3°			1 OF 1

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

K2-1127SN