

RoHS

Height(高度): NO.1

	J		T
	I		S
5.5	H		R
5.2	G		Q
4.8	F		P
4.5	E		O
4.3	D		N
3.8	C		M
3.5	B		L
3.1	A		K
高度H(mm)	X=	高度H(mm)	X=

Material:

Button 按钮	硅胶 (蓝色)
Cover plate 盖板	铜 (镀银)
Shrapnel 弹片	不锈钢 (复银)
Base 基座	PPA/LCP耐温280
Pin 引脚	磷铜 (镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA
Contact impedance(接触阻抗):	$\leq 100m\Omega$ MAX
Insulation impedance(绝缘阻抗):	$\geq 100M\Omega$ MIN
Welding resistance temperature(耐焊温度):	$250 \pm 5^{\circ}$ 5s
OPERATING LIFE(电气寿命):	300,000 cycles
Usage temperature(使用温度):	-25 to 85
Operating humidity(使用湿度):	$\leq 85\%$ RH
Trip(行程):	0.35 ± 0.1 mm
Operating force(操作力):	1 90 $\pm$ 30gf 2 130 $\pm$ 30gf 3 180 $\pm$ 50gf 4 250 $\pm$ 50gf 5 350 $\pm$ 50gf 6

NO.2

public errand (公差): ± 0.2 mm unit (单位): mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	SWITCH			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	K2-1156UP			CHECK	Z.LIU	REV.	A1
	UNIT :	TOLERANCE	UP TO 5	APPROVAL	DATE	K2-09-2019	
	mm	OTHERWISE	ABOVE 5 ~ 30				
			± 0.2 ± 0.3 ± 0.5 $\pm 3^{\circ}$	SCALE	2:1	PAGE	1 OF 1

K2-1156UP - □ - □