


RoHS

Height(高度) :

NO.1	
PART NO	H
A	1.80
B	1.87
C	1.92
D	2.00
E	2.50



Circuit diagram

Material:

Button 按钮	PBT/LCP耐温
Cover plate 盖板	铜 (镀银)
Shrapnel 弹片	不锈钢 (复银)
Base 基座	PBT/LCP耐温
Pin 引脚	磷铜 (镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA			
Contact impedance(接触阻抗):	≤ 100mΩMAX			
Insulation impedance(绝缘阻抗):	≥ 100MΩMIN			
Welding resistance temperature (耐焊温度):	250 ± 5 ° 5s			
OPERATING LIFE (电气寿命):	100,000 cycles			
Usage temperature (使用温度):	-25 to 85			
Operating humidity (使用湿度):	≤ 85% RH			
Trip(行程):	0.13 ± 0.05mm			
Operating force(操作力):	1	90 ± 30gf	2	130 ± 30gf
	3	180 ± 50gf	4	250 ± 50gf
	5	350 ± 50gf	6	
	NO.2			

NO.2

public errand (公差) : ± 0.2 mm unit (单位) : mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		SWITCH				DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.		K2-1809SN				CHECK	Z.LIU	REV.	A1
	UNIT :	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL		DATE	K2-09-2019
	mm		ABOVE 5 ~ 30	±0.3					
			ABOVE 30	±0.5					
			ANGLE	±3°		SCALE	2:1	PAGE	1 OF 1

K2-1809SN-□-□

B

A