

RoHS

Height(高度) :

NO.1			
PART NO	H	PART NO	H
O	11	P	11.5
Q	12	R	12.5
S	13	T	13.5
U	14	3	14.5
V	15	1	15.5
W	16	2	16.5
X	17	4	17.5
Y	18		

NO.2		
PART NO	L	L1
A	8	10
B	8.5	11
C	9	11
D	9.5	12
Γ	10	12

Material:

Button 按钮	LCP耐温280℃
Cover plate 盖板	磷铜 (镀银)
Shrapnel 弹片	不锈钢 (复银)
Base 底座	LCP 耐温 280℃
Pin 引脚	磷铜 (镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA	
Contact impedance(接触阻抗):	≤100mΩMAX	
Insulation impedance(绝缘阻抗):	≥100MΩMIN	
Welding resistance temperature(耐焊温度):	250±5 ° 5s	
OPERATING LIFE(电气寿命):	100,000 cycles	
Usage temperature(使用温度):	-25 °C to 85 °C	
Operating humidity(使用湿度):	≤85% RH	
Trip(行程):	0.25±0.1mm	
Operating force(操作力):	1	90±30gf
	2	130±30gf
	3	180±30gf
	4	250±30gf
NO.3	5	350±30gf
	6	

public errand (公差) : ±0.2mm unit (单位) : mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING		G.L CHEN		DWG.No.		LCZY	
PART NO.		K2-6645SP		CHECK		Z.LIU		REV.		A1	
	UNIT :	TOLERANCE OTHERWISE	UP TO 5 ABOVE 5 ~30 ABOVE 30 ANGLE	±0.2 ±0.3 ±0.5 ±3°	ANGLE 0°±3°	APPROVAL		DATE		K2-09-2019	
						SCALE		PAGE		1 OF 1	

K2-6645SP-□-□-□