






RoHS



Material:

contact pin插针	Au
plastic cement塑胶	Nylon尼龙/PA46
Pin 引脚	Au
CONTACT A(P脚A)	Au

P.C.B LAYOUT(Copper-side view)



Model No.	1	2	3
PIN	Ø2.0	Ø2.35	Ø2.5

Main technical specifications:

Rated load(额定负荷):	DC30V 0.5A
Contact impedance(接触阻抗):	≤100mΩMAX
Insulation impedance(绝缘阻抗):	≥100MΩMIN
Welding resistance temperature(耐焊温度):	250±5 ° 5s
OPERATING LIFE(电气寿命):	5,000 cycles
Usage temperature(使用温度):	-20 °C to 70 °C
Operating humidity(使用湿度):	≤85% RH
Insertion and Extraction Force(插拔力)	3~20N

public errand (公差) : ±0.2mm unit (单位) : mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	DC JACK	DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	DC-013	CHECK	Z.LIU	REV.	A1
UNIT : mm	TOLERANCE OTHERWISE UP TO 5 ABOVE 5 ~30 ABOVE 30 ANGLE ±0.2 ±0.3 ±0.5 ±3°	APPROVAL	SCALE	DATE	DC-09-2019
			2:1	PAGE	1 OF 1