




RoHS



P.C.B LAYOUT(copper-sided view)



DC-080-A	DC-080-B
	
	
	

Material:

contact pin插针	Au
plastic cement塑胶	Nylon尼龙/PA46
Pin 引脚	Au
CONTACT A(P脚A)	Au

Main technical specifications:

Rated load(额定负荷):	DC30V 0.5A
Contact impedance(接触阻抗):	$\leq 100\text{m}\Omega\text{MAX}$
Insulation impedance(绝缘阻抗):	$\geq 100\text{M}\Omega\text{MIN}$
Welding resistance temperature(耐焊温度):	$250 \pm 5^\circ\text{C}$
OPERATING LIFE(电气寿命):	5,000 cycles
Usage temperature(使用温度):	-20 to 70
Operating humidity(使用湿度):	$\leq 85\%\text{ RH}$
Insertion and Extraction Force(插拔力)	3~20N

public errand (公差): $\pm 0.2\text{mm}$ unit (单位): mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	DC JACK			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	DC-080			CHECK	Z.LIU	REV.	A1
	UNIT :	TOLERANCE OTHERWISE	UP TO 5	ANGLE	APPROVAL	DATE	DC-09-2019
			ABOVE 5~30				
	mm		ABOVE 30	$0^\circ \pm 3^\circ$	SCALE	PAGE	1 OF 1
			ANGLE				

DC-080-□

B

A