






RoHS



Material:

contact pin插针	Au
plastic cement塑胶	Nylon尼龙/PA46
Pin 引脚	Au
CONTACT A(P脚A)	Au

Main technical specifications:

Rated load(额定负荷):	DC30V 0.5A
Contact impedance(接触阻抗):	$\leq 100m\Omega$ MAX
Insulation impedance(绝缘阻抗):	$\geq 100M\Omega$ MIN
Welding resistance temperature(耐焊温度):	$250 \pm 5^\circ$ 5s
OPERATING LIFE(电气寿命):	5,000 cycles
Usage temperature(使用温度):	-20 to 70
Operating humidity(使用湿度):	$\leq 85\%$ RH
Insertion and Extraction Force(插拔力)	3~20N

public errand (公差): $\pm 0.2mm$ unit (单位): mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	DC JACK			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.	DC-085			CHECK	Z.LIU	REV.	A1
	UNIT :	TOLERANCE	ANGLE	APPROVAL	DATE		DC-09-2019
	mm	OTHERWISE	UP TO 5 ABOVE 5~30 ABOVE 30 ANGLE	SCALE	PAGE		1 OF 1

DC-085-□