

客户图 橙色

REV	LTR	DESCRIPTION	DATE	APPROVED
A0			20160406	LTY

备注:

1.材质:

1.1胶芯: LCP+30%G.F UL94V-0

1.2端子: C18140, T=0.12mm; 镍底, 镀金 $\times\mu$ "

1.3外壳: 不锈钢, T=0.30mm; 表面镀镍100 μ "
或亮锡100 μ "

2.主要特性:

2.1额定电流: 3A

2.2接触阻抗: 30m Ω MAX

2.3绝缘阻抗: 100M Ω MIN 250V DC

2.4耐压测试: 250V AC

2.5沾锡性: 温度250 $\pm$ 5 $^{\circ}$ C, 时间5iA0.5s

2.6整体插入力: 3.57kgf MAX

整体拔出力:0.6kgf MIN

2.7使用寿命: 5000次

2.8工作温度: -30 $^{\circ}$ C~+80 $^{\circ}$ C

PIN ASSIGNMENT:

PinNo.	SignalName	PinNo.	SignalName
A1	CND	B12	CND
A2		B11	
A3		B10	
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	D+	B7	D-
A7	D-	B6	D+
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10		B3	
A11		B2	
A12	CND	B1	CND

TOLERANCES		LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD			
.X	± 0.30	TITLE:			
.XX	± 0.20	TYPE-C母座短体插板贴片16P 无弹 尾部铆合			
.XXX	± 0.10	PARTNO. : 三次molding			
ANGLES	$\pm 1.00^{\circ}$	DRAWINGNO. : TYPE-C-31-M-31 橙色			
APPD. :		REV. :	SIZE:	UNIT:	SCALE:
CHECK:		A0	A4	MM	1:1
DRAWN:	LTY				SHEET:
					11

