







MODEL CODE



REV.	ECN.	NO.	APPD.



P.C.B LAYOUT
BOTTOM VIEW



CIRCUIT DIAGRAM



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	0.5A 50V DC
CIRCUIT	1P2T
CONTACT RESISTANCE	100m Ω MAX.
TIMING	NON-SHORTING
TRAVEL	3mm
OPERATING FORCE	180 $\pm$ 80gf
OPERATING LIFE(cycles)	10,000

8					WITHIN 1.5mm: ±0.1mm	UNITS mm	LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD				
7					OVER 1.5mm: ±0.2mm	MAT'L					
6	SPRING	STEEL WIRE	1	NATURAL		SEE NOTE	TITLE:	PART NO.:			
5	CONTACT	BRASS STRIP	1	Ag PLATED			SLIDE SWITCH / VERTICAL	SS-12F23			
4	TERMINAL	BRASS STRIP	3	Ag PLATED		FINISH	DR:	2015/05/22	DWG NO.:		
3	BASE	PHENOLIC RESIN	1	NATURAL		SEE NOTE	CHKD:	2015/05/22	ADL-12F23		
2	FRAME	STEEL STRIP	1	Ni PLATED	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.	Q'TY	APPD:	3:1	1/1	A	CUSTOMER DRAWING
1	KNOB	POM	1	BLACK							
NO.	PARTS	MATERIAL	Q'TY	FINISHING							